

Nenn Maß d	Schlüsselweite s		Festigkeit & Anziehmoment MA (Nm)				
	DIN	ISO	4.6	5.6	8.8	10.9	12.9
M 1	2,5						
M 1,2	3						
M 1,4	3						
M 1,6	3,2						
M 2	4						
M 2,5	5						
M 3	5,5						
M 3,5	6						
M 4	7		1,02	1,37	3,3	4,8	5,6
M 5	8		2	2,7	6,5	9,5	11,2
M 6	10		3,5	4,6	11,3	16,5	19,3
M 7	11						
M 8	13		8,4	11	27,3	40,1	46,9
M 10	17	16	17	22	54	79	93
M 12	19	18	29	39	93	137	160
M 14	22	21	46	62	148	218	255
M 16	24		71	95	230	338	395
M 18	27		97	130	329	469	549
M 20	30		138	184	464	661	773
M 22	32	34	180	250	634	904	1 057
M 24	36		235	315	798	1136	1 329
M 27	41		350	470	1176	1 674	1 959
M 30	46		475	635	1597	2274	2662
M 33	50		645	865	2161	3078	3601
M 36	55		1080	1440	2778	3957	4631
M 39	60		1330	1780	3597	5123	5994
M 42	65						
M 45	70						
M 48	75						
M 52	80						
M 56	85						
M 60	90						
M 64	95						
> M 64	-						

Downloaded from: www.R25-Bike.de

